



**SMART  
PLOT**

**Our Strength is  
Innovation**

## CONTACT

EMAIL  
[info@smartplot.com.tr](mailto:info@smartplot.com.tr)

WEBSITE  
[smartplot.com.tr](http://smartplot.com.tr)

PHONE  
+(90) 212 452 20 60



**SMART  
PLOT**

**SMARTPLOT**

**INNOVATIVE  
PEDESTAL  
SYSTEM**

## WHAT IS SMARTPLOT?

The SmartPlot is an innovative pedestal system designed for the installation of side-grooved wooden, WPC deck or stone. It is primarily used on railmounted aluminum frames, ideal for surfaces such as terraces, balconies, walkways, and other outdoor spaces.

## EASY AND SECURE INSTALLATION

This fastening system ensures that sidegrooved deck boards are securely fixed on to aluminum frames with C-channels using a rotating lock clip. The unique feature of the SmartPlot Aluminium Easyclips W system is that it eliminates the need for screws during installation, making the process quicker and more efficient.



SmartPlot pedestal has two types application: with aluminum frame for Decking or stone and from top adjustable for stone. Top Adjustment allows height adjustments directly from the top of the pedestal for ease of use. The stone is fixed by with joint clips.



On SmartPlot pedestal with aluminum frame for Decking; Rail system ensures that sidegrooved deck boards are securely fixed on to aluminum frames with C-channels. Aluminium Easyclips W system is that it eliminates the need for screws during installation.



Stone application can be done in 2 ways depending on the detail; from top Adjustment system allows height adjustments directly from the top of the pedestal or fixed by with joint clips with aluminium frame.

## TECHNICAL SPECIFICATIONS

**Material:** Aluminium frame and PP pedestal.

**Usage Areas:** Suitable for terraces, balconies, walkways, and other outdoor areas.

**Load Capacity:** Supports up to 1000 kg per unit.



## KEY FEATURES

The SmartPlot System offers a range of innovative tools and components designed for efficient, durable, and professional-grade installation of tiles and decking.



Provides automatic slope correction up to 5%, ensuring a perfectly even surface regardless of substrate irregularities.



Facilitates faster laying, reducing overall installation time and ensures rapid outflow of water, helping to prevent water stagnation.



Provides secure locking with adjustable hooks and flexible plate springs for a stable connection.



Enables quick and easy disassembly and reassembly, reducing maintenance time and effort.



SMART  
PLOT