



TECHNICAL SHEET OF CONFORMITY	SmartPI_15-30 ADJUSTABLE PEDESTALS	PAGE NO. 1/1 REV NO. 10 REV DATE. 17.03.2025
-------------------------------	---------------------------------------	--

\* The SmartPlot system uses Surplot raised flooring pedestals. SmartPlot products are composed of innovative accessories adapted to Surplot pedestals.

#### DEFINITION

- SMARTPLOT® pedestals are made of PP (polypropylene copolymer) and PVC
- 180 mm outer diameter of 1 base unit with a circular cutaway.
- 180 mm outer diameter of 1 head.
- The available height of SMARTPLOT® SmartPI\_15-30 screwjack pedestal is between 37 to 52 mm with a circular cutaway.

#### SPECIFICATIONS

TEST METHOD Row Material	STANDARD	UNIT	RESULTS &Tolerances
Determination of Density	TS-EN-ISO 1183-2	g/cm <sup>3</sup>	0,898±0.10
Hardness	TS -EN ISO 868	Shore A	85±5
Tensile Strength	TS EN ISO 527-1	Mpa	19,5
Elongation &Break	TS 1398-1 EN ISO 527-1	%	≥10
Determination of ash	TS 336 ISO 247	%	≤10

Visible Defects	-	-	None
Material	-	-	polypropylene copolymer
Colour	-	-	Black
Height	-	mm	37 to 52
Head diameter	-	mm	180
Base diameter	-	mm	180
Centric Load	-	kN	≤ 40
Visible cumulated threaded height (0 mm)	-		
Centric Load	-	kN	≥ 10
Visible cumulated threaded height (15 mm)	-	kN	≥ 10
Water Absorption (Fully diving method)	-	48 hrs	%0,1
Service Temperature	-	°C	-30 to 70

Prepared by IPM	Controlled by TQM	Confirmed by GM

TURKEY HEAD OFFICE: Yenibosna Mahallesi Doğu San. Sit.  
2. Blok. No:11 Bahçelievler/İSTANBUL  
Tel: +(90) 212 4522060 Fax: +(90) 212 4522027  
E-mail:info@smartplot.com.tr  
[www.smartplot.com.tr](http://www.smartplot.com.tr)

